

■ MB-6462K

■ MB-6042K




NC Boring Machine

WOODTECH

Panel Line




NC Drilling machine make machine adjustment more quickly and convenience, processing data can save in machine computer and use




Standard with PC, remote control available




High precise servo motor drill package and positioning unit movement, operator can input the data and machine auto move to right position.




Automatic drilling management software



X-direction servo automatic positioning



Y-direction servo automatic backing



Segmented storage

MODEL	MB-6462K	MB-6042K
Min Panel (L x W)	250 x 250 mm	250 x 250 mm
Max Panel (L x W)	3200 x 900 mm	3200 x 900 mm
Max depth of Vertical boring head	50mm	50mm
Working table Height	950mm	950mm
Machining length (X axis)	250-3200mm	250-3200mm
Machining width (Y axis)	250-900mm	250-900mm
Max distance of two horizontal boring holes position	640mm	640mm
Max depth of Horizontal boring head	40mm	40mm
Rotating speed of boring spindles	2800 RPM / 50Hz	2800 RPM / 50Hz
Max Working thickness	50mm	50mm
Bottom drilling Row	6 (11+11Heads)	6 (11+11Heads)
Top Drilling Row	4 (11+11Heads)	-
Horizontal drilling Head	2 (21 Heads)	2 (21 Heads)
Top Drill Head Power	8.8 Kw (1.1 x 8nos)	-
Bottom Drill Head Power	13.2 Kw (1.1 x 12nos)	13.2 Kw (1.1 x 12nos)
Horizontal Drill Head Power	3 Kw (1.5 x 2nos)	3 Kw (1.5 x 2nos)
Min distance of vertical drilling Row	128mm	128mm
Max distance of vertical drilling group	896mm	896mm
Working Pressure	0.6-0.8 MPA	0.6-0.8 MPA
Gross Weight	5000 kgs	4520 kgs
Total Power	36.45 kw	18.75 kw
Package Size (LxWxH)	5550 x 2270 x 2200 mm	5550 x 2270 x 2200 mm
Overall Size	5310 x 3120 x 2000 mm	5310 x 3120 x 2000 mm
Voltage	415V/50Hz/3P	415V/50Hz/3P